

## RYCO SRX Hose Release

RYCO is proud to release the new SRX Xtreme Suction and Return Hose.

SRX is extremely flexible and requires less force to bend.

SRX hose is available with a Black cover in sizes 3/4" to 3".

The Synthetic Rubber Black cover is oil and abrasion resistant.

SRX is recommended for petroleum and water-based hydraulic fluids in suction lines or in low pressure return lines.

The superior flexibility is advantageous in installations where space is minimal.

Use T4000 BITELOK Non-Skive one piece crimp couplings.

SRX Hose has a temperature range from -40°C (-40°F) to +100°C (+212°F).

For additional information please contact RYCO Product Management or your local RYCO representative.



SRX- XTREME SUCTION AND RETURN HOSE																	
PART NO	HOSE SIZE	NOMINAL HOSE ID		NOMINAL HOSE OD		MAXIMUM WORKING PRESSURE		MINIMUM BURST PRESSURE		MINIMUM BEND RADIUS		VACUUM RATING		AVERAGE WEIGHT		COUPLING SERIES	
Hose	DN	Dash	mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	mmHg	inHg	kg/m	lb/ft	NON-SKIVE
SRX12	19	-12	19,1	3/4	29.6	1.17	21	305	84	1,218	40	1.6	600	23	0,52	0.35	T4000
SRX16	25	-16	25,4	1	36.2	1.43	17	247	68	986	45	1.8	600	23	0,63	0.42	T4000
SRX20	31	-20	31,8	1.1/4	44.0	1.73	14	203	56	812	60	2.4	600	23	0,82	0.55	T4000
SRX24	38	-24	38,1	1.1/2	49.4	1.94	10	145	40	580	65	2.6	600	23	1,07	0.72	T4000
SRX32	51	-32	50,8	2	63.8	2.51	7	102	28	406	100	3.9	600	23	1,54	1.03	T4000
SRX40	63	-40	63,5	2.1/2	76.5	3.01	4	58	16	232	140	5.5	600	23	2,01	1.35	T4000
SRX48	76	-48	76,2	3	89.9	3.54	4	58	16	232	180	7.1	600	23	2,50	1.68	T4000

SUCTION & RETURN HOSE		T4000 COUPLINGS	
XTREME	CRIMP Ø	MARK LENGTH	
SRX	±0,20mm	mm	
SRX12	31,4	30	
SRX16	39,2	31	
SRX20	49,3	48	
SRX24	53,3	50	
SRX32	66,7	51	
SRX40	82,1	65	
SRX48	94,6	60	