

Type Approval Certificate Extension

This is to certify that **Certificate No.08/10093 (E3)** for the undernoted product(s) has/have been extended and renumbered in accordance with the relevant requirements of the Lloyd's Register Type Approval System.

This certificate is issued to:

PRODUCER RYCO Hydraulics.

PLACE OF RYCO Hydraulics Pty. Ltd.

PRODUCTION 99 Calarco Drive, Derrimut, Victoria, 3026 Australia

RYCO Hydraulics Sdn. Bhd.

Plot 207, Kuala Ketil Industrial Estate, 09300 Kuala Ketil,

Kedah Darulaman, Malaysia

RYCO Hydraulics (Dalian) Ltd.

38 Ying Ri Road, Ying Cheng Zi Industrial Zone, Gan Jing Zi District,

Dalian 116036 China

DESCRIPTION Flexible Hoses of Non-Metallic Material with Permanently Fitted

Couplings, <u>Designations:</u> Diehard H13D Slider H13S

TYPE SAE 100R13

APPLICATION For use on ships and offshore installations classed with Lloyd's Register, as

short lengths in systems of fresh and seawater, water based hydraulics,

pneumatics, fuel and lube oil.

Certificate No. 08/10093 (E4)

Issue Date 27 December 2018

Expiry Date 26 December 2023

Sheet 1 of 3

Chng Teck Wee
21 January 2022
Marine and Offshore
South Asia Technical Support Office
Engineering System
Lloyd's Register Singapore Pte. Nd.

Chng Teck Wee South Asia Technical Support Office Lloyd's Register Singapore Pte. Ltd.

Lloyd's Register Asia

2 Science Park Drive, #02-05/06 Ascent, Singapore 118222

Lloyd's Register Group Limited its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as the 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.



STANDARD Part 5, Chapter 12 of Lloyd's Register's Rules and Regulations for the

Classification of Ships (July, 2013)

Part 5, Chapter 10 of Lloyd's Register's Rules and Regulations for the Classification of Mobile Offshore Units (September 1996 plus Notices Nos. 1, 2,

3, 4, 5 & 6 as applicable)

Fire Resistant Testing according to ISO 15540/15541

RATINGS Sizes: DN 19 to DN 51 (see below)

Maximum Working Pressure: 350 bar (see below) Service Temperature: -40°C to +121°C (see below)

Coupling Material: Carbon Steel AISI

Stainless Steel (Option)

Electroplated Fe/Zn12c acc. to AS1789

OTHER CONDITIONS The hoses may be used for the following working conditions

DIEHARD H13D	DN (mm)	Max. Pressure (bar)	
H1312D	19	350	
H1316D	25	350	
H1320D	31	350	
H1324D	38	350	
H1332D	51	350	
Temperature Range: -40°C to +121°C			

SLIDER H13S	DN (mm)	Max. Pressure (bar)
-------------	---------	---------------------

Certificate No. 08/10093 (E4)

Issue Date 27 December 2018

Expiry Date 26 December 2023

Sheet 2 of 3

Chng Teck Wee
21 January 2022
Marine and Offshore
South Asia Technical Support Office
Engineering System
Lloyd's Register Singapore Pte. Vo.

Chng Teck Wee South Asia Technical Support Office Lloyd's Register Singapore Pte. Ltd.

Lloyd's Register Asia

2 Science Park Drive, #02-05/06 Ascent, Singapore 118222

Lloyd's Register Group Limited its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as the 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.



H1312S	19	350	
H1316S	25	350	
H1320S	31	350	
H1324S	38	350	
H1332S	51	350	
Temperature Range: -40°C to +121°C			

Where synthetic rubber hoses are used for oil fuel supply to burners, the hoses are to have external wire braid protection in addition to the integral wire braid

Carbon steel couplings are to be normalised for temperatures below -10°C.

In all cases the hoses are to be installed in accordance with the manufacturer's instructions and tested to the satisfaction of the attending surveyor.

"This Certificate is not valid for equipment, the design, ratings or operating parameters of which have been varied from the specimen tested. The manufacturer should notify Lloyd's Register Singapore Pte. Ltd. of any modification or changes to the equipment in order to obtain a valid certificate."

The **Design Appraisal Document No. 08/10093(E4)** and its supplementary Type Approval Terms and Conditions form part of this Certificate.

All other details remain as the previous **Certificate No. 08/10093(E3)** to which this extension should be attached.

Certificate No. 08/10093 (E4)

Issue Date 27 December 2018

Expiry Date 26 December 2023

Sheet 3 of 3

Chng Teck Wee
21 January 2022
Marine and Offshore
South Asia Technical Support Office
Engineering System
Lloyd's Register Singapore Ptc. Etc.

Chng Teck Wee South Asia Technical Support Office Lloyd's Register Singapore Pte. Ltd.

Lloyd's Register Asia

2 Science Park Drive, #02-05/06 Ascent, Singapore 118222

Lloyd's Register Group Limited its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as the 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.