

RY300 EVO

FULL SERVICE WORKSHOP
BENCHTOP; VERY HIGH CRIMP FORCE

KEY FEATURES

Crimp force of up to 300 tonnes for hoses up to 4"

Easy to use and robust

Automatic maintenance alerts

Groove for 90° long drop fittings

3.0 kW motor Single phase


Model shown equipped with SCS control panel




CONTROL OPTIONS AVAILABLE ON REQUEST



SC



SCE



SCS

TECHNICAL SPECIFICATIONS

CAPACITY*

Textile / Suction Hose: 4" max.

2wb: 3" max.

4ws: 2" max.*

6ws: 1 1/2" max.*

CRIMP RANGE

4 - 130 mm (0.157 - 5.118")

CRIMP FORCE

300 t

OPENING WITH DIES

+54 mm (+2.125")

COMPLETE OPENING

180 mm (7.086")

MASTER DIE LENGTH

115 mm (4.523")

STANDARD DIES

14, 16, 19, 22, 26, 30, 34,
39, 45, 51, 57

NOISE LEVEL

<70 dB A

VOLTAGES

220/240 V, 1Ph, 50-60 Hz

MOTOR

3 kW
(Required mini 20A installation)

DIMENSIONS

765 x 400 x 750 mm

(30 x 16 x 30")

NET WEIGHT

262 kg (578 lb)

TECHNICAL FEATURES

- Automatic maintenance alerts
- Cylinder protection against dust
- durable design

*Indicative capacities depending on hose and fitting type

OPTIONAL



Maintenance Kit



Marking Dies



Die Storage Panel



Die Storage Table



Electrical Footswitch

Quick Change
GunAluminium Quick
Change GunMechanical
BackstopDie Sets for Brake
& Air Conditioning
HosesDie Storage Panel
EVO