



JETSTORM

Pressure Washer Hose

JS4000 / JS6000

RYCO JETSTORM JS6000 AR

JS4000BX / JS6000BX

RYCO JETSTORM JS6000BX AR

JS4000G / JS4000GX
JS6000G / JS6000GX

RYCO JETSTORM JS6000GX AR

HOSE

JETSTORM PRESSURE WASHER

JS6000/G/BX/GX

JETSTORM
PRESSURE WASHER
420 BAR/6100 PSI



RECOMMENDED FOR:

Hot Water Pressure Washer Machines operating at high pressures.

Not recommended for Steam.

PERFORMANCE:

Meets or Exceeds the Performance Requirements of: EN 1829-2.

TUBE:

Black, heat resistant synthetic rubber.

REINFORCEMENT:

Two braids of high tensile steel wire.

COVER:

Oil resistant synthetic rubber formulated to resist marking.

PART NO	COLOUR	PROPERTY
JS6000	Black	Highly abrasion resistant (AR) non marking.
JS6000G	Grey	Animal fat resistant (AFR) non marking
JS6000BX	Blue	Highly abrasion resistant (AR) non marking.
JS6000GX	Grey	Highly abrasion resistant (AR) non marking.

Embossed layline for positive, permanent identification. No skiving required for T2000 Series BITELOK Crimp Couplings.

TEMPERATURE RANGE:

JS6000/G/BX/GX JETSTORM Hoses handle hot water up to +135°C (+275°F) with intermittent service to +150°C (+302°F).

WORKING PRESSURE:

Maximum working pressures are based on 3:1 safety factor (maximum working pressure to minimum burst pressure).

COUPLINGS:



BITELOK NON-SKIVE ONE-PIECE CRIMP T2000 series (sizes -04 to -08).

For coupling specifications and assembly instructions see the latest RYCO Product Technical Manual - Hydraulics and the latest Crimp Chart on our website, www.RYCO.com.au

A MEMBER OF
THE AUSTRALASIAN HIGH PRESSURE
WATER JETTING ASSOCIATION

JS6000 JETSTORM PRESSURE WASHER HOSE																	
PART NO		HOSE SIZE		NOMINAL HOSE ID		NOMINAL HOSE OD		MAXIMUM WORKING PRESSURE		MINIMUM BURST PRESSURE		MINIMUM BEND RADIUS		AVERAGE WEIGHT		COUPLING SERIES T2000 ONE PIECE	
Hose	Hose	DN	Dash	mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	NON-SKIVE	
JS6004	JS6004G	6	-04	6,3	1/4	12,4	0.49	420	6100	1260	18300	50	2.0	0,23	0.15	T2000	
JS6005	JS6005G	8	-05	7,9	5/16	14,5	0.57	420	6100	1260	18300	55	2.2	0,30	0.20	T2000	
JS6006	JS6006G	10	-06	9,5	3/8	16,3	0.64	420	6100	1260	18300	65	2.6	0,32	0.22	T2000	
JS6008	JS6008G	12	-08	12,7	1/2	19,3	0.76	420	6100	1260	18300	90	3.6	0,44	0.30	T2000	
JS6004BX	JS6004GX	6	-04	6,3	1/4	13,5	0.53	420	6100	1260	18300	50	2.0	0,26	0.17	T2000	
JS6005BX	JS6005GX	8	-05	7,9	5/16	15,6	0.61	420	6100	1260	18300	55	2.2	0,34	0.23	T2000	
JS6006BX	JS6006GX	10	-06	9,5	3/8	17,4	0.69	420	6100	1260	18300	65	2.6	0,35	0.24	T2000	
JS6008BX	JS6008GX	12	-08	12,7	1/2	20,4	0.80	420	6100	1260	18300	90	3.6	0,49	0.33	T2000	

Cutting and Assembly Charges apply to all RYCO industrial hoses, and vary by hose types and sizes. Contact RYCO for additional information or visit www.RYCO.com.au

RYCO QUALITY

JS4000/G/BX/GX

JETSTORM
PRESSURE WASHER
280 BAR/4100 PSI



RECOMMENDED FOR:

Hot Water Pressure Washer Machines.

Not recommended for Steam.

PERFORMANCE:

Meets or Exceeds the Performance Requirements of:
EN 1829-2.

TUBE:

Black, heat resistant synthetic rubber.

REINFORCEMENT:

One braid of high tensile steel wire.

COVER:

Oil resistant synthetic rubber formulated to resist marking.

PART NO	COLOUR	PROPERTY
JS4000	Black	Highly abrasion resistant (AR) non marking.
JS4000G	Grey	Animal fat resistant (AFR) non marking
JS4000BX	Blue	Highly abrasion resistant (AR) non marking.
JS4000GX	Grey	Highly abrasion resistant (AR) non marking.

Embossed layline for positive, permanent identification. No skiving required for T2000 Series BITELOK Crimp Couplings.

TEMPERATURE RANGE:

JS4000/G/BX/GX JETSTORM Hoses handle hot water up to +135°C (+275°F) with intermittent service to +150°C (+302°F).

WORKING PRESSURE:

Maximum working pressures are based on 3:1 safety factor (maximum working pressure to minimum burst pressure).

COUPLINGS:



BITELOK NON-SKIVE ONE-PIECE CRIMP T2000 series (sizes -04 to -08).

For coupling specifications and assembly instructions see the latest RYCO Product Technical Manual - Hydraulics and the latest Crimp Chart on our website, www.RYCO.com.au

A MEMBER OF
THE AUSTRALASIAN HIGH PRESSURE
WATER JETTING ASSOCIATION

JS4000 JETSTORM PRESSURE WASHER HOSE																	
PART NO		HOSE SIZE		NOMINAL HOSE ID		NOMINAL HOSE OD		MAXIMUM WORKING PRESSURE		MINIMUM BURST PRESSURE		MINIMUM BEND RADIUS		AVERAGE WEIGHT		COUPLING SERIES T2000 ONE PIECE	
Hose	Hose	DN	Dash	mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	NON-SKIVE	
JS4004	JS4004G	6	-04	6,3	1/4	11,5	0.45	280	4100	840	12300	50	2.0	0,15	0.10	T2000	
JS4005	JS4005G	8	-05	7,9	5/16	13,1	0.52	280	4100	840	12300	55	2.2	0,18	0.12	T2000	
JS4006	JS4006G	10	-06	9,5	3/8	15,3	0.60	280	4100	840	12300	65	2.6	0,23	0.15	T2000	
JS4008	JS4008G	12	-08	12,7	1/2	18,3	0.72	280	4100	840	12300	90	3.6	0,31	0.21	T2000	
JS4004BX	JS4004GX	6	-04	6,3	1/4	12,6	0.50	280	4100	840	12300	50	2.0	0,18	0.12	T2000	
JS4005BX	JS4005GX	8	-05	7,9	5/16	14,2	0.56	280	4100	840	12300	55	2.2	0,22	0.15	T2000	
JS4006BX	JS4006GX	10	-06	9,5	3/8	16,4	0.65	280	4100	840	12300	65	2.6	0,26	0.17	T2000	
JS4008BX	JS4008GX	12	-08	12,7	1/2	19,4	0.76	280	4100	840	12300	90	3.6	0,36	0.24	T2000	

Cutting and Assembly Charges apply to all RYCO industrial hoses, and vary by hose types and sizes. Contact RYCO for additional information or visit www.RYCO.com.au

RYCO LOCATIONS

AUSTRALIA

+61 1300 111 247
Sales@RYCO.com.au

GLOBAL HEAD OFFICE MELBOURNE

19 Whitehall Street
Footscray, VIC 3011

REGIONAL LOCATIONS

ADELAIDE

BL Shipway & Co
217 Richmond Road
Richmond, SA 5033

BRISBANE

97 Northlink Place
Northgate, QLD 4013

BLACKWATER

6 Jarrah Street
Blackwater, QLD 4717

NEWCASTLE

14 Ironbark Close
Warabrook, NSW 2304

PERTH

47 Tacoma Circuit
Canning Vale, WA 6155

NEW ZEALAND

+64 800 842 872
Sales@RYCOnz.co.nz

NEW ZEALAND HEAD OFFICE AUCKLAND

Unit 1, 707 Great South Road
Penrose, Auckland 1061

USA & CANADA

+1 866 821 7926
Sales@RYCO.us

HEAD OFFICE USA & CANADA TEXAS

1616 Greens Road
Houston, Texas 77032

REGIONAL LOCATIONS

CALIFORNIA

1150 Valencia Avenue
Tustin, California 92780

ONTARIO

32 Airpark Place
Guelph, ONT
Canada N1L 1B2

IOWA

1007 West 10th Street
Pella, Iowa 50219

CHINA

DALIAN: +86 411 8886 0006
SHANGHAI: +86 512 3306 6181
Sales@RYCO.cn

DALIAN

38 Yingri Road
Ying Cheng Zi Industrial Zone
Gan Jing Zi District
Dalian 116036

SHANGHAI

2nd Building, 88 Dalian East Road
Taicang Economy Developing Area
Taicang, Jiangsu Province 215400

RYCO 24•7 SERVICE CENTRES

RYCO 24•7 133•24•7 Sales@RYCO247.com.au

NSW

Bellingen
Boggabri
Gregory Hills
Gunnedah
Ingleburn
Mascot
Newcastle
Penrith
Rutherford
Wallerawang
Woodburn

QLD

Archerfield
Banana
Blackwater
Brisbane
Clermont
Dysart
Eagle Farm
Ipswich
Moranbah
Narangba
Rocklea
Rolleston

SA & NT

Adelaide
Cowell
Darwin
Kadina
Kapunda
Loxton
Port Pirie
Richmond
Riverland
Roxby Downs
Whyalla

VIC & TAS

Bendigo
Melbourne
Mildura
Shepperton
Warrnambool
Devonport
Launceston

WA

Kalgoorlie
Mandurah
Newman
Perth
Port Hedland

RYCO 24•7 0800•111•24•7 Sales@RYCO247.co.nz

NORTH ISLAND

Gisborne
Hamilton
Hastings
Kaikohe
Manawatu
Masterton
Matamata
Morrinsville
New Plymouth
Opoutama
Otorohanga
Palmerston North
Pukekohe
Putaruru
Taupo
Tauranga

Waipawa
Wellesford
Wellington
Whakatane
Whangarei
Whitianga

SOUTH ISLAND

Christchurch
Blenheim
Bluff
Dovedale
Dunedin
Golden Bay
Gore
Invercargill
Nelson
Thornbury
Timaru
Westport
Winton

RYCO 24•7 1 844•700•0247 Sales@RYCO247.us

BOSSIER CITY

3210 Shed Road
Bossier City
LA 71111

HAMMOND

6718 Kennedy Av
Hammond
IN 46323

MICHIGAN CITY

1306 West
Highway 20
Michigan City
IN 46360

Tel +1 318 747 7926 Tel +1 219 844 6570 Tel +1 219 844 6570

SINGAPORE	MALAYSIA	LATIN AMERICA	SOUTH AFRICA
SINGAPORE 6 Battery Road Level 42, Six Battery Road 049909 Tel: +65 6483 5655 Email: Sales@RYCO.com.sg	PENANG Plot 207 Kuala Ketil Ind. Estate Kuala Ketil, Kedah, 09300 Tel: +60 4 415 2500 Email: Sales@RYCO.com.sg	LIMA, PERU Av. La Encalada 569 Of. 201-A C.C. Monterrico Surco Lima 33 Tel: +51 1 435 8323 Email: Ventas@RYCO.com.pe	JOHANNESBURG 340 Roan Crescent Corporate Park North Randjespark, Midrand 1685 Tel: +27 10 4100 500 Email: Sales@RYCO.co.za